

▶ Powerful Performance & Incredible Efficiency

Built from guiding principle, HiTi P720L was designed to maximize your photofinishing profits by increasing uptime, shortening printing time, and providing multi-applications. HiTi P720L is recommended to use with HiTi Picvite Suite, which is easy and with less investment to create your highly scalable and profitable photofinishing business.

Shortening Printing Time

Roll-fed mechanism design with HiTi outstanding printing technology gets 4"x6" (10x15cm) prints within 7.9 seconds*

* Under the conditions of HiTi laboratory testing.

Increasing Uptime

By 1000-print capacity design, HiTi P720L is much less often in changing media, and gives more selling time. Also, high capacity roll reduces staff interruption.



Fitting in Multi-Applications

With full front-access design, HiTi P720L can be integrated in unattended or semi-attended Kiosk system at retail. With HiTi Picvite Suite, HiTi P720L, as a micro mass photofinishing system, is capable of competing against silver halide.



Superior Printing Performance

Powered by HiTi Color


With HiTi Color Technology inside, HiTi P720L is the preferred brand of photo printers by many photo and imaging professionals as well as enthusiasts around the world.



Hassle-free Operation

By straightforward instruction, getting HiTi P720L ready is not laborious any more.

media change required!



Color Optimization

HiTi Color Technology offers two color preferences for different printout request. HiTi Passport Photo Color produces superior skin tones in portrait; HiTi Classic Color provides brilliant life-like true color reproduction for your digital images.



Diverse Print Formats

HiTi P720L allows most diversity in print sizes, including 4"x6", 4'x6"-2UP, 5"x7", 5"x7"-2UP, 6"x8", 6"x9" and 6"x9"-2UP*.

Prime Quality in Matte Finish


Apart from glossy photos, HiTi P720L is capable of matte finish. No

*2UP function should be operated from printer driver



Appearance

dibuperusac.com





- (1) Operation Panel
- (2) Waste Paper Box
- 3 USB Connector
- (4) Power Connector
- (5) Power Switch
- (6) Paper Setting Indicator

Specifications

Model Name	HiTi P720L
Printing Method	Dye Diffusion Thermal Transfer (D2T2 Technology)
Resolution	300 x 300 dpi
Printing Size & Capacity*	4"x 6" (102 x 152 mm): 1000 prints 5"x 7" (127 x 177 mm): 600 prints 6"x 8" (152 x 203 mm): 455 prints 6"x 9" (152 x 229 mm): 455 prints 4"x 6" -2UP 5"x 7" -2UP 6"x 9" -2UP
Printing Speed**	4"x 6" approx. 7.9 seconds 5"x 7" approx. 12 seconds 6"x 8" approx. 15 seconds 6"x 9" approx. 15 seconds
PC-Link Operation	Yes
Recommended Software	Picvite Kiosk (Express) Picvite Minilab (Express)
Operation System	Windows 2000/ XP/ Vista/ Windows 7 Mac OS 10.2, 10.3, 10.4, 10.5 and 10.6
PC Connection	USB 2.0 Hi Speed
Power Requirement	AC 100 V ~240 V, 50/ 60 Hz, 6 A
Operation Environment	10°C ~ 35°C (50°F ~ 95°F); 20 ~90% non-condensing
Power Consumption	Total power consumption: approx. 500W Standby power consumption: approx. 20W
Dimension (W x H x D)	330 x 424 x 425 mm (13x16.7x16.7 inches)
Weight	26.7 kg / 58.9 lbs (consumable excluded)

- * 2UP function should be operated from printer driver.
- ** Under the conditions of HiTi laboratory testing.

Dimension



▶ Consumables

P720 Series



P720 Series



P720 Series







